



**Ultimate Load Capacities for Zinc & Nylon Drywall Anchors in Wallboard (\*AKA EZ-Anchor®)<sup>1</sup>**

Anchor	3/8" Wallboard		1/2" Wallboard		5/8" Wallboard		3/4" Wallboard	
	Tension lbs.	Shear lbs.	Tension lbs.	Shear lbs.	Tension lbs.	Shear lbs.	Tension lbs.	Shear lbs.
Zinc Drywall	45	60	60	70	75	100	80	100
Nylon Drywall	40	50	50	55	65	70	70	80

The values listed above are ultimate load capacities which should be reduced by a minimum safety factor of 4.0 or greater to determine the allowable working load.

**Allowable Load Capacities for Zinc & Nylon Drywall Anchors in Wallboard (\*AKA EZ-Anchor®)<sup>1</sup>**

Anchor	3/8" Wallboard		1/2" Wallboard		5/8" Wallboard		3/4" Wallboard	
	Tension lbs.	Shear lbs.	Tension lbs.	Shear lbs.	Tension lbs.	Shear lbs.	Tension lbs.	Shear lbs.
Zinc Drywall	10	15	12	20	15	25	15	25
Nylon Drywall	10	15	12	15	15	20	15	25

1. Allowable load capacities listed are calculated using an applied safety factor of 4.0.

\* EZ-Anchor® is a Registered trademark of Illinois Tool Works.